

HTL SERIES KIT

24V DC High Output - Tape Light Kit

High Output tape light kits provide the components for a complete Trulux Lighting System. The High Output Kit offers an impressive amount of lumens while staying highly energy efficient. This convenient kit is ideal for undercabinet lighting or other similar task lighting applications where brightness is needed.


- · Ready to install 24V Tape Light kit with plug & play connection
- Features handheld remote for easy on/off operation
- 2700K or 3000K color temperatures with 96+ CRI
- Up to 300Lm per foot consuming only 4.6W per foot
- Cuttable every 3.94" with max runs up to 16.4ft
- Includes 3A plug-in power supply with in-line receiver
- · Additional tape light accessories included for easy installation
- cULus Listed (dry location)
- 50,000 hours rated life







| HTL-5MKIT SERIES QUICK SPECS | |
|------------------------------|--------------------------------------|
| | |
| VOLTAGE | 24V DC |
| WATTAGE | 4.6W / ft |
| LUMENS | Up to 310Lm / ft |
| CCT OPTIONS | 2700K / 3000K |
| CRI | 96+ |
| MAX RUN | 16.4 ft |
| CUTTING POINTS | 3.94" (100mm) |
| IP RATING | IP54 - Coated |
| DIMMING | Via Handheld Remote Control (5-100%) |
| DIMENSIONS | 0.39" (10mm) W x 0.06" (1.65mm) H |
| BEAM ANGLE | 120° |
| OPERATING TEMP | 5°C (41°F) to 70°C (158°F) |
| CERTIFICATIONS | cULus Listed - Dry / Damp Location |
| RATED LIFE | 50,000 Hours |







HTL-5MKIT SERIES IP RATINGS



IP54 (Coated)

Features a light nano-coating applied to the tape light and LED's that protects from moisture and dust. **Best suited:** Indoor dry & damp locations

HTL SERIES QUICK LOOK



16.4ft Max Run



HTL-5MKIT SERIES ORDERING INFORMATION ITEM NUMBER VOLTAGE CCT LENGTH LUMENS / FT WATTAGE / FT IP RATING CRI **CUTTING** MAX RUN HTL-UWW-5MKIT 24V DC 2700K 16.4 ft 285Lm / ft 4.6W / ft IP54 96+ 3.94" (100mm) 16.4 ft HTL-WW-5MKIT 24V 3000K 16.4 ft 310Lm / ft 4.6W / ft IP54 96+ 3.94" (100mm) 16.4 ft



HTL-5MKIT includes: (1) 24V DC Plug-in Power Supply / (1) 15ft (20/2) Wire Spool (1) In-line RF Receiver / (1) Handheld Remote / (6) HD Power Feeds / (3) HD Splice Connectors

HTL-5MKIT QUICK SET-UP



24V High Output Tape Light

| HTL-5MKIT SERIES ACCESSORIES | | |
|------------------------------|---|--|
| ITEM NUMBER | DESCRIPTION | |
| TL-CONKIT | Trulink 4-in-1 Connection Kit | |
| TL-BLKS | Trulink 4-in-1 Connector Block (QTY 10) | |
| TL-2PWR-HD | HD Power Feed (IP54) | |
| TL-2JUMP6-HD | 6" HD Linking Cable | |
| TL-2JUMP24-HD | 24" HD Linking Cable | |
| TL-2SPL-HD | HD Tape to Tape Splice Connector | |
| WIRE-15-2PIN | 15ft (20/2) Wire Spool | |
| WIRE-CMP-100-3PIN | 100ft (16/3) In-wall Rated Wire Spool | |
| INLINE-SC-CTRL | Simple Select In-line Controller (Single Color) | |
| LVSB-2PIN | In-Line Splice Terminal Block | |
| RCWY-PVC-1M | 1m Plastic Wire Cover Raceway (White) | |



WIRE-15-2PIN

TL-CONKIT TL-BLKS









TL-2SPL-HD







