

drinking water cartridges



carbon impregnated cellulose

- ★ Economically priced
- ★ Dual purpose cartridge provides bad taste, odor, and chlorine taste & odor reduction, as well as sediment filtration*
- ★ Design maximizes dirt holding capacity
- ★ For municipal/chlorinated water (not recommended for well water applications)
- ★ Recommended for point of use filtration



The W5CIP is Tested and Certified by NSF International.



granular activated carbon (GAC)

- ★ Effective taste, odor, and chlorine taste & odor reduction
- ★ Cartridge design ensures that water passes through the entire length of the carbon bed, maximizing contact time.
- ★ Reduces particles as small as 20-micron in size by mechanical means



carbon block cartridges

- ★ Excellent for bad taste, odor, and chlorine taste & odor reduction*
- ★ Specialty blocks are capable of reducing lead and certain volatile organic compounds (VOCs)*
- ★ NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.



The W.5CB and WLC-R are Tested and Certified by NSF International.

* As tested by American Plumber
Certain states require system
registration or certification for
health-related reduction claims

| | | housings | | | | | | | | | | | | | | | | | | |
|----------------|------------------|-----------------|-------------------------|--------------|---------------|---------------|----------------|------------------------|--------------|----------------|---------------|-------------|---------------|------------------------|------------|----------------------|------------|------------|------------|----|
| Drinking Water | | Micron Rating † | 3/8" SlimLine® Housings | W385-PR (5") | W38-PRA (10") | W38-PRB (10") | W38-PRQC (10") | 3/4" Standard Housings | W34-PR (10") | WC34-PRB (10") | WC34-PR (10") | WVC34 (10") | W34-PRB (10") | 3/4" High Temp Housing | WH34 (10") | 3/4" Stainless Steel | ST-1 (10") | ST-2 (20") | ST-3 (30") | |
| cartridges | Filter Cartridge | | Flow Rate* (gpm) | | | | | | | | | | | | | | | | | |
| | W.5CB478 | 0.5 | 1 | | | | | | | | | | | | | | | | | |
| | W5CIP478 | 5 | 1 | | | | | | | | | | | | | | | | | |
| | WGC478 | — | 1 | | | | | | | | | | | | | | | | | |
| | W.5CB | 0.5 | | 1 | 1 | 1 | | | | | | | | | | | | | | |
| | WLC-R | 0.5 | | 0.6 | 0.6 | 0.6 | | | | | | | | | | | | | | |
| | W5CIP | 5 | | 5 | 5 | 5 | | 5 | 5 | 5 | 5 | 5 | | | 5 | | | 5 | 10 | 15 |
| | WCC | — | | 1 | 1 | 1 | | | | | | | | | | | | | | |

† Micron ratings are nominal

* Flow rates are calculated for cartridges according to the housing in which they are being used

| Model | Part | Medium | Micron Rating (nominal) | Max. Flow Rate (gpm) | Diameter | Length |
|---|------|--------|-------------------------|----------------------|----------|--------|
| Carbon Impregnated Cellulose - reduces particles as small as 5 micron in size by mechanical means | | | | | | |

| | | | | | | |
|----------|-----------|------------------------------|---|---|--------|--------|
| W5CIP478 | 155022-52 | Carbon Impregnated Cellulose | 5 | 2 | 2-1/2" | 4-7/8" |
| W5CIP | 155002-52 | Carbon Impregnated Cellulose | 5 | 5 | 2-5/8" | 9-3/4" |

| Model | Part | Medium | Chlorine Taste & Odor Reduction @ Flow Rate** | Max. Flow Rate (gpm) | Diameter | Length |
|---------------------------------|------|--------|---|----------------------|----------|--------|
| Granular Activated Carbon (GAC) | | | | | | |

| | | | | | | |
|--------|-----------|-----------------------------------|---------------------|---|--------|--------|
| WGC478 | 155110-51 | Granular Activated Carbon | >750 Gal. @ 0.5 GPM | 1 | 2-7/8" | 4-7/8" |
| WCC | 155155-51 | Granular Activated Coconut Carbon | >500 Gal. @ 1 GPM | 1 | 2-7/8" | 9-3/4" |

| Model | Part | Medium | Reduces** | Micron Rating (nominal) | Chlorine Taste & Odor Reduction @ Flow Rate** | Lead (gallons) | VOCs (gallons) | Max. Flow Rate | Diameter | Length |
|---|------|--------|-----------|-------------------------|---|----------------|----------------|----------------|----------|--------|
| Carbon Block - reduces particles as small as 5 micron in size by mechanical means | | | | | | | | | | |

| | | | | | | | | | | |
|----------|-----------|------------------------|---|-----|------------------------|-------|-------|-----|--------|--------|
| W.5CB478 | 155169-51 | Acid-washed Bituminous | Chlorine Taste & Odor, Cyst | 0.5 | >3,000 Gal. @ 1 GPM | N/A | N/A | 1 | 2-7/8" | 4-7/8" |
| W.5CB | 155162-51 | Acid-washed Bituminous | Chlorine Taste & Odor, Cyst | 0.5 | >20,000 Gal. @ 1 GPM | N/A | N/A | 1 | 2-7/8" | 9-3/4" |
| WLC-R | 155268-51 | Acid-washed Bituminous | Chlorine Taste & Odor, Cyst, Lead & VOC | 0.5 | >20,000 Gal. @ 0.6 GPM | 600** | 300** | 0.6 | 2-7/8" | 9-3/4" |

** As tested by American Plumber Certain states require system registration or certification for health-related reduction claims



5730 NORTH GLEN PARK ROAD
MILWAUKEE, WISCONSIN 53209
Phone 800.645.5428 • Fax 888.588.9388
www.americanplumber.com