For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

P1-**DL/ P3-**DL PEX Toilet Riser - One-Piece with Compression Sleeve or Insert

Use: For use in potable water distribution systems in accessible locations only

Design Features:

- One-piece construction
- Cut-to-Length for clean, professional installation

Operating Specifications:

Temperature:40°- 180° FPressure:125 PSI maximum

Tubing Diameter: 0.375" OD or 0.50" OD

CONNECTOR MATERIAL SPECIFICATIONS		
Tube	Cross-linked Polyethylene (PEX)	
Compression Sleeve (3/8" OD)	РОМ	
Compression Insert (1/2" OD)	Stainless steel	

PART DIMENSIONS (Inches)				
Model	DIM. A	DIA. B		
P1-12DL	11.56	.38		
P1-15DL	14.56	.38		
P1-20DL	19.56	.38		

Model DIM. A DIA. B P3-15DL 14.56 .50 P3-20DL 19.56 .50

Part Listing:

P1-12DL F	3/8" OD tube x 11-1/2" length, flag label
P1-15DL	3/8" OD tube x 14-1/2" length
P1-20DL	3/8" OD tube x 19-1/2" length
P1-20DL F	3/8" OD tube x 19-1/2" length, flag label
P3-15DL	1/2" OD tube x 14-1/2" length
P3-20DL	1/2" OD tube x 19-1/2" length
P3-20DL F	1/2" OD tube x 19-1/2" length, flag label

Listings & Certifications:

 IAPMO listed to ASME A112.18.1 / CSA B125.1 (including NSF/ANSI372 and NSF61)



This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

400.212 P1-DL/P3-DL PEX Toilet Riser w/Comp Sleeve or Insert REV 9.19



R

©2019 Brasscraft Manufacturing Company

