For Residential and Commercial Applications							
Job Name		Engineer / Architect					
Job Location		Wholesaler					
Submittal Date		Contractor					

PLB104/115X

1/4 Turn Angle Stop – Barbed PEX Inlet

Use: For use only in potable water distribution systems, hot and cold, in accessible locations only

Part Listing:


□ PLB104X B
□ PLB104X B
□ PLB104X P
□ PLB104X P
□ PLB115X P
□ PLB115X P
1/2" nom crimp barb (for PEX) x 3/8" OD compression, chrome plated, bagged
□ 1/2" nom crimp barb (for PEX) x 1/4" OD compression, chrome plated, bagged



STOP MATERIAL SPECIFICATIONS				
Body	Brass, plated			
Stem	Brass			
Ball	Brass, plated			
Seats	PTFE			
O-ring	Rubber			
Handle	ABS, plated			
Handle Screw	Stainless steel			
Compression Nut	Brass, plated			
Compression Sleeve	Brass			
Adaptor	Brass, plated			

Operating Specifications				
Temperature	Pressure			
Intermittent 40°- 140° F	125 PSI maximum			

PART DIMENSIONS (Inches)								
Model	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F		
PLB104X	2.02	1.77	2.23	1.12	1.10	.94		
PLB115X	2.02	1.77	2.23	1.12	1.12	.94		



A B 3/8"OD Comp E E

Listings & Certifications:

 IAPMO listed to ASME A112.18.1 / CSA B125.1 (includes NSF/ANSI 372 and NSF61)





This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.