



A Moen Incorporated Brand



Model: CA40514 Series with spray.  
CA40512 Series without side  
spray



## One Handle Kitchen With Spray (Quick Install)

### DESCRIPTION

- Metal construction with various finishes identified by suffix
- Hose reach 34", hose length 48", Quick Connection
- CA40514: Chrome finish, white spray, white spray escutcheon
- CA40514C: Chrome finish, chrome spray, chrome spray escutcheon
- 24" flexible supplies with 3/8" compression fittings
- Six (6) individual boxes per master carton

### OPERATION

- Pivot action, lever-style handle
- Temperature control by 90° arc
- Will operate with less than 5 lbs. of force

### FLOW

- Spout flow limited to 1.5 gpm (5.7 L/min) at 60 psi

### CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and plastic material
- Single body construction for easy replacement

### NOTE


- CA40514 series is designed to install through 4 holes 1-1/4" (32mm) MIN. DIA. and 4" (102mm) on center

### STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1, and all applicable requirements referenced therein, including NSF61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65, and the Federal Safe Drinking Water Act
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- Feature red/blue hot/cold temperature indicators
- ADA for lever handle

### WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information



CLEVELAND FAUCET GROUP • 25300 AL MOEN DRIVE • NORTH OLMDST, OHIO 44070 • (888) 450-5522 • www.cfgonline.com