

# Assembly Instruction Sheet #S-8012P24C For Style 8012P24C

**Tools Required:** Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.

**Light Source:** (10) E12 Candelabra Base Bulbs 60W Medium (Not Included).  
**Estimated Assembly Time:** 20-30minutes  
**Preparation:** Identify and inspect all parts before beginning installation. Check package content list and diagrams before to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

**Warnings and Cautions**  
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

**Package Contents**

	14mm*3PCS 40mm*1PCS		14mm*7PCS
	14mm*2PCS 40mm*1PCS		14mm*1PCS 40mm*1PCS
	14mm*8PCS		14mm*3PCS 40mm*1PCS
	40mm*1PCS		14mm*11PCS
	14mm*13PCS 40mm*1PCS		40mm*1PCS
	14mm*13PCS 40mm*1PCS		40mm*1PCS

**Hardware Contents**

PART	DESCRIPTION	QUANTITY
BB	Wire nut	2pcs
EE	Outlet Box Screw	2pcs

**STEP 1 - Install Strap Iron to Fixture Body**

Figure 1

**STEP 2 - Install Metal frame to Fixture Body.**

Figure 2

**STEP 3 - Install the Fixture Chain and Ceiling Canopy**

Figure 3

- Outlet Box
- Hex Nut
- Lock Washer
- Crossbar
- Outlet Box Screw
- Nipple
- Canopy Chain Loop
- Ceiling Canopy
- Canopy Lock Ring

**STEP 5 - Wire Connections**

A. Use standard wire connectors (not included) to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.

Figure 5

- White wire from outlet box
- Black wire from outlet box (or Red)
- White wire from fixture
- Black wire from fixture
- Ground wire from outlet box
- Ground wire from fixture
- Bar, or Green Ground wire from outlet box
- Ground wire from fixture
- Green Ground Screw on the Crossbar

**STEP 4 - Install the Fixture Chain and Ceiling Canopy**

Figure 4

- Supply/DN/Wires and Ground Wire
- Nipple
- Canopy Chain Loop
- Ceiling Canopy
- Canopy Lock Ring
- Fixture Loop

**STEP 6 - Install Crystals and bulb.**

Figure 6

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8

E12 Bulbs  
Not Include