

Qwik Caps

Quick, reusable caps for pipe ends, testing & cleanouts



Technical Data

- Underground or above-ground applications
- Complies to ASTM D 5926
- 300 stainless steel clamps
- Maximum operating temperature: 140°F intermittent
- Maximum test pressure: 4.3 PSI
- Permanent seal
- Fast, easy solution



Nominal Qwik Caps

| Part Number | I.D. | Min. | Max. | Material |
|---------------|-------|-------|-------|--|
| QC-101 | 1.86 | 1.61 | 1.95 | 1 1/2" PL, CI, Copper or ST |
| QC-102 | 2.34 | 1.94 | 2.48 | 2" PL, CI, Copper or ST or 1 1/2" Durion |
| QC-103 | 3.48 | 3.09 | 3.63 | 3" PL, CI, Copper or ST |
| QC-104 | 4.47 | 3.96 | 4.60 | 4" PL, CI, Copper, ST or Triple Wall |
| QC-105 | 5.57 | 5.03 | 5.85 | 5" PL, CI, Copper or ST or 4" Clay or Concrete |
| QC-106 | 6.30 | 5.73 | 6.62 | 6" PL, CI, Copper, ST or SS or 5" EC, OB, AC or Concrete |
| QC-108 | 8.63 | 7.70 | 9.11 | 8" PL, CI, Copper, ST or SS or 6" WC |
| QC-10 (TC-10) | 10.47 | 9.88 | 11.00 | 10" PL, CI, Copper, ST or SS or 8" Concrete |
| QC-112 | 12.49 | 11.41 | 13.33 | 12" PL, CI, ST, Ductile or AC or 10" WC, EC or Concrete |

| Part Number | I.D. | Min. | Max. | Material |
|-------------|-------|-------|-------|---|
| QC-0.85 | 0.85 | 0.79 | 0.91 | 1/2" PL or ST or 3/4" Copper or SS |
| QC-1.07 | 1.07 | 1.00 | 1.12 | 3/4" PL or ST or 1" Copper or SS |
| QC-1.38 | 1.37 | 1.22 | 1.50 | 1" PL or ST or 1 1/4" Copper or SS |
| QC-1.68 | 1.68 | 1.37 | 1.87 | 1 1/4" PL or ST or 1 1/2" Copper or SS |
| QC-2.75 | 2.75 | 2.18 | 2.93 | 2" Durion |
| QC-3.75 | 3.76 | 3.29 | 4.00 | 3" Durion or 4" SS |
| QC-4.75 | 4.82 | 4.32 | 5.05 | 4" Durion, Ductile, OB or Corrugated or 5" SS |
| QC-7.00 | 6.96 | 6.44 | 7.25 | 5" WC or 6" Ductile, AC, OB or Corrugated |
| QC-9.00 | 9.01 | 8.59 | 9.34 | 8" Ductile, OB, AC or Corrugated |
| QC-9.75 | 9.75 | 9.29 | 10.00 | 8" WC or EC |
| QC-10.75 | 10.74 | 10.22 | 11.15 | 10" Ductile, AC or Corrugated |
| QC-14.00 | 14.00 | 13.23 | 14.30 | 12" Concrete or Clay or 14" PL |

Flexible Couplings

Qwik Caps offer a quick, easy way to cap pipe ends, cleanouts and test pipes. Made of flexible PVC, they are suitable for above-ground or underground applications on cast iron, steel, copper or plastic piping.

WC: West Coast Clay
 EC: Eastern Standard Clay
 OB: Orangeburg
 PL: Plastic

CI: Cast Iron
 AC: Asbestos Cement
 ST: Steel
 SS: Stainless Steel