

# BILLOWS

 Ceiling mounted • Dry location listed **PROGRESS LED**

## Description:

The 52" Billows ceiling fan features an LED light kit with white opal glass shade and five reversible blades. With a sophisticated and traditional design, the Billows offers both form and function with two energy efficient 10W MaxLite LED lamps, featuring a 3000K color temperature.

## Specifications:

- Antique Bronze (-20) (painted)
- Steel construction
- Frosted bowl
- 52" 5 Blade Fan with LED light
- Oversized, textured die cast hanger ball reduces noise and wobble vibrations
- Mounting hardware is included
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- 54 in of wire supplied
- American Walnut/Cherry reversible blades, plywood construction
- with Walnut fob
- Antique Bronze pull chain 13.5 degree blade pitch
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately. Triple capacitor speed control, manual reverse control
- Airflow: 4682 CFM\*
- Energy consumption: 59 watts (excluding lights)\*
- Airflow efficiency: 79 cfm/watt\*
- \* Fan on a downrod

## Performance:

Number of Modules	2
Input Power	10w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	800/80 (LM-79) per module
CCT	3000 K
CRI	90+
Life (hours)	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed

## P2552-20

## Images:



## Dimensions:

Diameter: 52"  
Height: 17-1/2"

