

Temp

Ceiling Mounted • Dry Location Listed **PROGRESS LED**



Description:

This ceiling fan offers industrial inspiration in a sleek, modern design perfect for giving your favorite living space a little extra light and feeling of comfort. Five plywood blades rotate around the fan's center column. An LED light source covered in a prismatic glass shade is ready to offer generous illumination.

Specifications:

- Clear double cut prismatic glass Bowl
- An LED light source covered in a prismatic glass shade is ready to offer generous illumination.
- Five plywood blades rotate around the fan's center column.
- This ceiling fan offers industrial inspiration in a sleek, modern design perfect for giving your favorite living space a little extra light and feeling of comfort.
- Ideal for any living room, great room, or bedroom.
- Perfect for farmhouse or rustic settings.
- Measures 52-inch width by 16-1/4-inch height.
- Uses one LED module that is included (17w max).
- 3-speed remote control with battery included.
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 6.5 in W., 2.5 in ht., 6.5 in depth
- Mounting strap for outlet box included
- 80 in of wire supplied

Performance:

Number of Modules	1
Input Power	17 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1,386/77 (LM-82)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
Max. Operating Temp	40 °C
Warranty	Limited Lifetime Warranty
Labels	UL Dry Location Listed
	Meets California Title 24 JA8-2016
	AC motor

P2578-16330K



Dimensions:

Diameter: 52 in
Height: 16-1/4 in

Clear double cut prismatic glass Bowl
Width: 10.6 in
Height: 3.3 in

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$11

\$3 | | | \$34

Cost Range of Similar Models (19" – 84")

• Based on 12 cents per kWh and 6,4 hours use per day
• Your cost depends on rates and use
• Energy Use: 41 Watts

Airflow

3,198

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
• Airflow Efficiency: 78 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy

P2578-16330K

Dimming Notes:

P2578-16330K is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron	NTEVL-300
Lutron	DVELV-300P
Lutron	Caseta Wireless
Leviton	6672
Leviton	6674
Lutron	AYCL-153P
Lutron	AYLV-600P
Lutron	MAELV-601
Leviton	AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.