

GREER

Ceiling mounted • Dry location listed

Description:

This five-blade 54" Greer ceiling fan complements either industrial or farmhouse decor. It comes with a wire meshed shade light kit that uses two vintage LED lamps (Included) and remote control with batteries are also included. Hang it on a flat or slopped ceiling with its dual mount system.

Specifications:

- Antique Nickel (-81) (Painted)
- Steel construction
- 54" Greer indoor ceiling fan features five blades and an LED light source, offering both form and function with energy- and cost-savings benefits
- Wire meshed shade light kit included uses two 5.5W vintage LED lamps (included)
- 2200K color temperature 80CRI and 450 lumens
- The Greer ceiling fan features reversible Walnut/Driftwood blades and an Antique Nickel motor finish
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- The five-blade Greer fan features a dual mount system to offer greater flexibility when installing
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- Remote control may be replaced by a P2630-30 wall control
- A 3/4" x 6" downrod is included. Longer accessory downrods can be ordered separately
- High Speed Energy Information: Airflow- 4794 cfm, Energy consumption- 64 watts (excluding lights), Airflow efficiency- 75 cfm/watt
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- Walnut/Driftwood reversible blades, plywood construction
- 12 degree blade pitch
- Full Function Remote Included
- Triple capacitor speed control, manual reverse control
- This product is not available for sale into the State of California.

Performance:

Number of Lamps	2
Input Power	6.5w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	450/69 (LM-79) per module
CCT	2200 K
CRI	96 CRI
Life (hours)	15,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime
Labels	ULus Dry location listed
	Meets California Title 24 high efficacy requirements

P2584-81

Images:



Dimensions:

Diameter: 54"
Height: 21-7/8"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$11

\$3
\$34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- **Your cost depends on rates and use**
- Energy Use: 40 Watts

Airflow

3,320

Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move
- Airflow Efficiency: 82 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy

P2584-81**Dimming Notes:**

P2584 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.