

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



P350007-009-30



Description:

One-light 15 inch LED Flush Mount in Brushed Nickel features a white linen glass bowl. Fixtures are dimmable to 10 percent with Triac, phase forward or ELV dimmers. 3000K and 90 CRI.

Images:

Specifications:

- · Brushed Nickel (-009) (plated)
- · Steel Construction
- Etched White Linen glass bowl
- 1389 lumens 50 lumens/watt (delivered)
- 3000k color temperature, 90+ CRI
- · TM-21 54,000 hour life.
- · Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- · 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016




Performance:

Number of Modules	1	
Input Power	28w	
Input Voltage	120 V	
Input Frequency	50/60 Hz	
Lumens/LPW (Source)	2409/88 (LM-82)	
Lumens/LPW (Delivered)	1389/50 (LM-79)	
CCT	3000 K	
CRI	90 CRI	
Life (hours)	54,000 (L70/TM-21)	
FCC	FCC Title 47, Part 15, Class B	
Min. Start Temp	-25 ℃	
Max. Operating Temp	25 ℃	
Warranty	5 year warranty	
Labels	ETL Damp location listed	
	ENERGY STAR® qualified	
	Meets California Title 24 JA8-2016	

Dimensions:

Diameter: 15" Height: 5-7/8"





One-Light LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



P350007-009-30

Dimming Notes:

P350007 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Leviton 6674

Lutron AYLV-600P

Lutron NTLV-600

Lutron MAELV-601

Leviton AWRMG-EAW

Lutron N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.