

Fixture Type:		
Fixture Type:		

Contact:

Globe LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED



Description:

A distinctive classic globe pendant is accented by a striking metal black cap. The cap holds a beautiful opal glass shade ready to emit gentle illumination. This versatile pendant can be displayed as a single fixture or in groups of two or more to create a custom lighting design for your home.

Specifications:

- · Opal glass Globe
- The cap holds a beautiful opal glass shade ready to emit gentle illumination.
- A distinctive classic globe pendant is accented by a striking metal black cap.
- This versatile pendant can be displayed as a single fixture or in groups of two or more to create a custom lighting design for your home.
- · Ideal for any foyer, kitchen, or dining room.
- Perfect for mid-century modern, transitional, modern, or contemporary settings.
- · Measures 8-inch width by 9-3/4-inch height.
- · Uses one LED module (9w max).
- · Compatible with many Triac/ELV dimmers (see dimming controls)
- · Includes installation instructions and mounting hardware.
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.5 in W., 1 in ht., 5.5 in depth
- \cdot 1/8 IP mounting plate for outlet box included
- 120 in of wire supplied

Performance:

Number of Modules	1	
Input Power	9 W	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	624/66 (LM-82)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	60000 (L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15, Class B	
Warranty	5-year Limited Warranty	
Labels	cCSAus Damp Location Listed	
	ENERGY STAR® qualified	
	Meets California Title 24 JA8-2016	

P500147-031-30




Dimensions:

Diameter: 8 in Height: 9-3/4 in

Overall Ht. W/Cord: 122 in

Opal glass Globe Width: 8 in Height: 7-1/2 in





Globe LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED



Dimming Notes:

P500147-031-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

P500147-031-30

Dimming Controls:

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Leviton SureSlide 6672

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.