

| Fixture Type: | | | | |
|---------------|--|--|--|--|
|---------------|--|--|--|--|

Globe LED

Ceiling cord Mounted · Damp Location Listed PROGRESS LED

Contact:



Description:

A distinctive classic globe pendant is accented by a striking metal brushed bronze cap. The cap holds a beautiful opal glass shade ready to emit gentle illumination. This versatile pendant can be displayed as a single fixture or in groups of two or more to create a custom lighting design for your home.

Specifications:

- · Opal glass Globe
- · The cap holds a beautiful opal glass shade ready to emit gentle illumination.
- A distinctive classic globe pendant is accented by a striking metal brushed bronze cap.
- This versatile pendant can be displayed as a single fixture or in groups of two or more to create a custom lighting design for your home.
- · Ideal for any foyer, kitchen, or dining room.
- · Perfect for mid-century modern, transitional, modern, or contemporary settings.
- Measures 11-5/8-inch width by 13-1/2-inch height.
- Uses one LED module that is included (17w max).
- · Compatible with many Triac/ELV dimmers (see dimming controls)
- · Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.5 in W., 1 in ht., 5.5 in depth
- 1/8 IP Mounting Plate
- 120 in of wire supplied

Performance:

| Number of Modules | 1 |
|---------------------|------------------------------------|
| Input Power | 17 W |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 1,276/73 (LM-82) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60000 (L70/TM-21) |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Warranty | 5-year Limited Warranty |
| Labels | cCSAus Damp Location Listed |
| | ENERGY STAR® qualified |
| | Meets California Title 24 JA8-2016 |
| | |

P500148-109-30




Dimensions:

Diameter: 11-5/8 in Height: 13-1/2 in

Overall Ht. W/Cord: 136-1/2 in

Opal glass Globe Width: 11-5/8 in Height: 10-1/2 in





Globe LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED



Dimming Notes:

P500148-109-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

P500148-109-30

Dimming Controls:

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Lutron Lumea LG-603PG

Leviton SureSlide 6672

Leviton SureSlide 6674

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Pass & Seymour Harmony DCL453PTCCCV6

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron Maestro MA-600

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.