

| Project: | | |
|---------------|--|--|
| Fixture Type: | | |
| Location: | | |
| Contact: | | |

LED Pendant

Ceiling cord mounted • Dry location listed PROGRESS LED





Description:

One-light LED pendant features designer oriented details. Brushed Nickel finish with polished white interior. 3000K, 90+ CRI, 623 lumens (source).

Specifications:

- Brushed Nickel (-09) (plated)
- · Steel Construction
- Satin Aluminum, painted white inside aluminum shade, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- · Designer oriented details.
- · Sleek design.
- · Brushed Nickel finish with polished white interior.
- 623 lumens 69.2 lumens/watt per module (source)
- · 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- · Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified

Performance:

| Number of Modules | 1 |
|------------------------|-------------------------------------|
| Input Power | 9w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 623/69.2 (LM-82) |
| Lumens/LPW (Delivered) | 323/42.5 (LM-79) |
| ССТ | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60,000 (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cCSAus Dry location listed |
| | ENERGY STAR® qualified |
| | |

P5175-0930K9

Images:



Dimensions:

Diameter: 6-1/2" Height: 8-7/8"

Overall Ht. W/Cord: 130"

Glass Width: 6-1/2" Glass 2 Width: 2-7/8" Length: 2-7/8" Height: 0-13/16"



LED Pendant

Ceiling cord mounted • Dry location listed PROGRESS LED



P5175-0930K9

Dimming Notes:

P5175 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.