

## 3IN Cylinders

Ceiling Mounted • Damp Location Listed PROGRESS LED



### Description:

3" White Surface Mount Modern Adjustable LED Cylinder

### Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.1 in W., 1.3 in ht., 5.1 in depth
- Mounting Plate
- 6 in of wire supplied

### Performance:

Input Power	12 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	986/82 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

# P550139-030-30



### Dimensions:

Diameter: 5 in  
Height: 7-3/8 in



**Photometrics:**

---

# P550139-030-30

<b>ELECTRICAL DATA</b>	<b>P550139-030-30</b>
Input Voltage	120 V
Input Frequency	60 Hz
THD	<20%
EMI/RFI	FCC Title 47, Part 15, Class B
Operating Temperature	-40 °C to 40 °C
Dimming	Yes*

\*See Dimming Notes for more information

**Dimming Notes:**

---

P550139-030-30 is designed to be compatible with many ELV/Reverse Phase Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

Lutron\_Diva DVELV-300P

Lutron\_Diva DVELV-300P

Lutron\_Caseta Wireless

Leviton\_SureSlide 6672

Lutron\_Ariadni AYCL-153P

Lutron\_Toggler TGCL-153PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

# P550139-030-30