

Project:		
Fixture Type:		
Location:		
Contact:		

# One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED





# **Description:**

Westport LED offers traditional styling to complement a variety of home decor options. A durable die-cast aluminum frame cradles a softly diffused seeded glass shade. 3000K, 90+ CRI 623 lumens (source). One-light LED wall mount.

### **Specifications:**

- · Antique Bronze (-20) (powder coat paint)
- Die-cast aluminum Construction
- Etched Seeded glass shade
- LED Module is replaceable (part # 93054049)
- · Traditional styling.
- Softly diffused seeded glass shade.
- Complements many home decor styles with beaded detailing.
- · 623 lumens 69.2 lumens/watt (source)
- · 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

#### **Performance:**

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	316/40.5128205128205 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements
	for outdoor use only

# P5863-2030K9

#### Images:



#### **Dimensions:**

Width: 9" Depth: 10-3/8" Height: 12-7/8" H/CTR: 3-3/4"

Glass Width: 7" Length: 7" Height: 5-3/4"



# One-Light Outdoor



P5863-2030K9

## **Dimming Notes:**

P5863 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.