Job Name/Title:_____ Catalog Number_____
Contractor:_____ Notes:_____

Rigid Elbows
45° - Galvanized Steel

Features
- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications
- For a secure connection to Rigid conduit; bend enables directional changes in conduit

Standard Material
- Galvanized steel

Standard Finish
- Hot dip galvanized

c UL us
E223147
1/2" to 4" meet UL 6 and ANSI C80.1
Federal Specification WW-C-563



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/ Case	(A) Min. UL Radius	(B) Straight Leg Each End
11	33300	1/2"	---	50	26	4	2.875
12	33310	3/4"	---	50	38	4.50	2.875
13	33320	1"	---	35	45	5.75	3
14	33330	1-1/4"	---	30	60	7.25	3.25
15	33340	1-1/2"	---	15	45	8.25	3.625
16	33350	2"	---	15	68	9.50	4.1875
17	33360	2-1/2"	1	50	400	10.50	5.25
18	33370	3"	1	40	455	13	5.8125
19	33380	3-1/2"	1	35	560	15	6.75
20	33390	4"	1	35	770	16	6.9375
20A	86293	5"	1	42	1840	24	8.125
20B	86294	6"	1	36	2556	30	13.25